Check Stab Instruments

L'esperienza nella stabilità tartarica

Experience in tartaric stability

D119 pHMeter

D119 pHMeter

Ail ph-metro/Rx-metro Termometro modello D119 è un apparecchio realizzato con le più avanzate tecnologie elettroniche, che hanno fatto uno strumento leggero e di dimensioni ridotte, ma con la stessa affidabilità degli strumenti da laboratorio. La solida cassa in ABS, la tastiera a membrana resistente all'acqua ed una pratica valigetta per il trasporto ideale per le misure su campo. Grazie al microcontrollore RISC, al display alfanumerico e al software, l'uso è immediato e l'operatore può selezionare la misura desiderata con l'ausilio di un solo tasto.
Durante l'uso come pH-metro o Redox-metro, se è inserita la sonda PT100 si ha la compensazione automatica della temperatura del liquido in esame, se lo strumento non rileva la presenza del sensore PT100, passa automaticamente dal modo "Compensazione Automatica" al modo "Compensazione Manuale".
Particolarmente curato nel design l'apparecchio si presenta con un ottimo aspetto estetico e funzionale; una vasta gamma di accessori contribuisce inoltre ad allargarne le prestazioni ed il campo di impiego

The ph meter/ Rx meter Thermometer model D119 is a device that has been designed with the latest electronic technology, with a compact, light weight dimension but with the same efficiency of a laboratory instrument.
The solid case in ABS, with the keyboard in a water resistance membrane is the ideal practical container for travel and working on the job site. Thanks to the micro controller RISC, the alpha numeric display and software, it is immediately usable.
The user can select the measurement desired with the use of only one key.
During the use as pH meter or Redox meter, if a probe PT100 is inserted, the automatic compensation of the temperature of the sample liquid is activated.
If the device does not detect the presence of the probe, it will automatically be set from the "Automatic Compensation" mode to "Manual Compensation" mode.
The device has an attractive aspect as well as functionality. There is a vast range of accessories to increase its utility in the field.

Campo pH Range pH	0-14 pH 0-14 pH
Campo Redox Range Redox	-1000mV / +1000mV -1000mV / +1000mV
Campo Temperatura Range Temperature	-50°C / +150°C -50°C / +150°C
Indicatore Indicator	LCD r.i. LED LCD r.i. LED
Contenitore Case	ABS ABS
Alimentazione Power supply	a Batteria Battery
Peso Weight	220 gr 220 gr

I dati contenuti nel presente depliant hanno carattere indicativo e possono essere variati, a discrezione del Costruttore, in qualsiasi momento e senza obbligo di preavviso
Data given in this brochure are indicative and can vary at the discretion of the manufacturer at any time and without obligation or notice

Rivenditore Autorizzato - Authorized Distributor

Delta Acque del Dott.A.Cavallucci
Via della Treccia N°37 - 50145 Firenze - It
Tel. (+39),055,319554/5Fax.(+39),055,316441
www.checkstab.com
info@checkstab.com
C.F. CVLLRT43E15B832B - P.IVA 00538550484 - C.C.I.A.A. FI N°231628 - AIA FI N°63501